

Designed by Robert Dudley Best

PRODUCT



Don't polish the brass

DESCRIPTION

Bestlite has been in continuous production since 1930. Robert Dudley Best created Bestlite design. He was highly influenced by the Bauhaus. In the past 80 years, people appreciated the lamps and it decorates many homes, hotels and restaurants worldwide. Loved by architects, designers and design aficionados throughout its 80-year history, today, Bestlite enjoys global iconic status.

VERSION - BESTLITE WALL LAMP BL7

Shade: Charcoal black, Matt-White, Grey, Brass, or Bone China
 Tube, arm, and foot base: Brass with lacquered surface
 Fabric wire - Brass colour

RAL codes are indicative.

- Charcoal black/Brass / White inside // RAL 9011 / RAL 9003 // Gloss level 10 / Gloss level 20
- Grey/Brass / White inside // RAL 2604005 / RAL 9003 // Gloss level 10 / Gloss level 20
- Brass/Brass / White inside // - / RAL 9003 // - / Gloss level 20
- Matt-White/Brass / White inside // RAL 9003 / RAL 9003 // Gloss level 10 / Gloss level 20
- Glossy Bone China/Brass

Please contact us for other colours or finishes.

VERSION

Order item - look for part number in the pricelist.

Series contains the following:

BL5, BL6, BL7, BL10

COLOURS



// Charcoal black / Brass

// Grey / Brass



// Matt-White / Brass

// All Brass



// Bone China / Brass

FACTS

MEASUREMENT - L X W X H inches

- Lamp height: 11,4 inches
- Tube length: -
- Shade height: 5,5 inches
- Shade diameter: Ø6,3 inches
- Cord - total length w/sw: App. 94,5 inches
- Cord - exposed out of lamp: App. 78,7 inches

WEIGHT ITEM - LAMP INCL. WIRE

489 g

PACKAGING TYPE

White cardboard box w/ 5ply corrugated

PACKAGING MEASUREMENT - L X W X H CM

L:10,2 x W:11 x H:7,8 inches

WEIGHT PACKAGING - MATERIAL TYPE

- Paper Egg crate: 280,5 g
- PE polybag: 60 g
- Cardboard inside: 26 g
- Cardboard outside: 206 g

WEIGHT PACKAGING - TOTAL

1001 g

NUMBER OF PARCELS

1 pcs.

LIGHT SOURCE

- Socket: E12 base
- Recommended light source: *All LED and fluorescent light bulbs*
- Recommended wattage: 9 W = (40 WATT incandescent bulbs)
- Max wattage: 13 W

- Recommended light source: *Halogen light bulb*
- Recommended wattage: 28 W = (40 WATT incandescent bulbs)
- Max wattage: 30 W

- All lamps can be fitted with a dimmer.
 Please contact your local electrician.

- Lightbulb not included

CLEANING AND MAINTENANCE

Use a soft damp cloth when cleaning your Bestlite lamp. Do not use household cleaners.

ACCESSORIES

-

ENVIRONMENT

-

TESTS

-

CERTIFICATION AND LABELS



ON DEMAND - (ordered at an additional charge)

ORDERING - BL7

Cord, switch on the wallbracket. US plug

- US plug: Type A, 2 PIN, 15 amp, (NEMA 1-15)

- US voltage: 120 V

- Frequency: 60 Hz

- Supply voltage: AC power ~

- Normally Closed: IP20



Class II / Double insulated

KOMPONENTS

01 // Shade Ø16 cm.

05 // E14 lamp holder

10 // Insulating ring

11 // Internal shade ring

12 // External shade ring

13 // Lamp holder cover

15 // Universal joint

17 // Bestlite arm

38 // Textile covered cord

41 // Push button switch

42 // Cover for push button switch

46 // Wall bracket

49 // Screw 9x19 mm.

51 // Mounting plate Ø7 cm

58 // Plug

MATERIAL

Shade: Charcoalblack, White or Grey

Tube and arm: Brass with lacquered surface

Textile covered cord

Shade and base: Brass with lacquered surface

Tube and arm: Brass with lacquered surface

Textile covered cord

INSTALLATION INSTRUCTIONS

Instructions document: No. 10-20-006-01.

The Bestlite key:

It's a practical tool that enables you to fasten the lamp arm. Simply use it like a screwdriver in the slot in the Bestlite nut.

Technical information:

Light source: CAUTION! TO REDUCE THE RISK OF FIRE, USE MAX. 40 WATT INCANDESCENT, E12, type B bulbs (220V 25W AC ONLY). Alternatively, max. 30W halogen bulbs. Turn always off when changing light bulbs.

The lamp is not appropriate for outdoor use or use in damp/wet rooms.

Some advice on cleaning your Bestlite:

Powder coated parts – base/bracket and shade:
Wash the parts with a damp cloth soaked in warm water and a bit of mild detergent.

Chrome plated parts:
Wash the chrome parts in damp cloth and wipe dry to bring up lustre.

If the surface is dirty, use a metal polish made especially for aluminium or other soft metals.

Use only soft cloths for wiping and polishing, never sponges or steel wool.

Do not use abrasive household cleaners.

Do not use acidic or alkaline cleaning materials, glass cleaner or household ammonia.

Dear Bestlite customer,
Congratulations on your Bestlite!
You have chosen a genuine design classic, which has been in continuous production for more than 75 years.

On the other side of this leaflet you will find some useful instructions for the use of your Bestlite.

Should you have any questions, please feel free to e-mail us at gubi@gubi.com or visit us at www.gubi.com.

Best regards,
Bestlite

001-0730v

BESTLITE
BY GUBI

BESTLITE • GUBI, Kubensvej 7-1, DK-2150, Nordhavn, Denmark • www.gubi.com

1. Shade
2. Glass
3. Internal ring
4. Light bulb

The shade fits and seals.

Wall mounting:

Choose and install inside the spot canopy.

Pre-drilling and use of plugs in the wall is recommended.

Mount the plate (5) – make sure you use appropriate screws designed for your wall as the plate carries the weight of the lamp.

When the plate is fastened to the wall – attach the Bestlite to the plate.

The wall mounting plate:

Two holes, above and below, respectively, mark the position of the wall through 'Bestlite' – use independent corner and plug.

Two threaded bolts, mount on the top through these, use the provided 'Bestlite' – use independent corner and plug.

Position of these two holes SHOULD always be horizontal.

Mounting the plate on the wall. Horizontal fit in the lamp is only brought in by the plate's design.

Connect the lamp wire to the supply wires (2).

Be sure to connect all grounding wires (green) to the same wire (1). Wire nuts or other connections are not to be used.

Lock wires carefully inside the edge of the canopy and secure the lamp on the wall BRACKET.

Position canopy and the lamp on the wall. Be careful not to damage any wires and do not force the canopy into the wall as this could cause the lamp to fall.

Place light bulb in lamp and turn (4) the power on.

10-20-006-01 Mounting plate BL 7 US